

LETO HB MIDI



INDUSTRIAL

Features:

- Suspended mounting (1m cable length)
- IP65 (dust tight & water jet proof)
- IK08 (5 joules) shock resistance
- Energy efficient Osram LEDs
- Available in 5700K (daylight)
- Ambient temperature -20° to 40°
- CRI >80
- Average 100,000 hrs LED life - L80 B10
- 80° optical reflector as standard

Options:

- Integral 3hr maintained emergency
- Dimming versions available
- Programmable driver
- 120° optical reflector - on special request
- 3000K (warm white) or 4000K (cool white) LED colour temperature available - on special request

Accessories:

- Suspension kit - on special request

Material:



- Body: die-cast aluminium

Colour:

- 04 Grey



Technical & Photometrics



Leto HB Midi							Ordering Code
Wattage	Colour Temperature	Delivered Lumens	Luminous Efficacy	Emergency Lumens	Beam	Weight (Kg)	
70W LED	5700K	8640lm	123lm/W	302lm	80° (Sym)	6.1	30-171-460-604
100W LED	5700K	12150lm	122lm/W	303lm	80° (Sym)	6.1	30-172-460-604
150W LED	5700K	18360lm	122lm/W	293lm	80° (Sym)	6.1	30-173-460-604
Options				Weight (Kg)	Add to Ordering Code		
Emergency (3 hour)				0.11	E3-		
1-10V (analogue)					/DA		
DALI (digital) dimming					/DD		
Programmable driver					/PD		

